

PRODUCT DESCRIPTION

The PiSys™ Flex is a fully pneumatic closed loop grit blasting and recycling unit to be used with other Pinovo® closed loop grit blasting tools. The unit comes in two different versions, V1 and V2, with pressure vessel sizes of 20 l and 50 l, respectively.

No significant clean-up or further work is required following the Pinovo® preparation process, the surface is ready for painting or other post-treatment.

The low noise and dust free Pinovo® surface preparation process minimizes the impact on surrounding trades and equipment.

Reuse of blast media reduces abrasive media consumption significantly.




TOOL PROPERTIES

Size:	Blast unit: 80 x 60 x 150 cm (V1) / 90 x 60 x 195 cm (V2) Suction unit: 80 x 60 x 170 cm
Weight (empty):	Approx. 210 kg (V1) / 225 kg (V2)
Pressure vessel size:	20 l (V1) / 50 l (V2)
Maximum working pressure:	8 bar
Compressed air requirements:	7 bar, dried compressed air 6 Nm ³ /min (standard system with PiWalk tool)
Air inlet:	1,5" Chicago Clawcoupling
Temperature range:	2 – 50°C

ABRASIVE BLAST MEDIA

Pinovo® Blasting Grit
Grit size F 12 and smaller

HEALTH AND SAFETY

Noise level:	$L_{pA} \leq 72$ dB at 1m distance (NS 4815-2:2006)
Conformity:	CE  II 2G Ex h IIA T6 Gb

ENVIRONMENT

Contamination:	Zero emission to surroundings
Waste management:	Closed loop waste management system

ACCESSORIES

Compatible with the following Pinovo® closed loop grit blasting tools:

- Standard system: PiPoint™, PiConnect™, PiCo Pipe™, PiWalk™ and Pihab™

Bergen – Norway
June 29, 2017

PINOVO AS reserves the right to make changes due to technical improvements. Photos may differ from actual product. Non-binding document.